

# Key Operated Pushbutton Switch 16.5A 400Vac



16.5(8)A 400Vac T85, (50,000 Operations)



15.5A 250Vac & 125Vac, (6,000 Operations)  
 125Vac & 250Vac 1/2hp & 11/2hp (6,000 Operations)  
 0.5A 30Vdc (6,000 Operations)  
 UL 85°C  
 Approvals applied for.



Compliant

- ▶ 400Vac, 16.5A, 50,000 Operations
- ▶ 125V, 1/2HP & 11/2HP, 6,000 Operations
- ▶ Double pole momentary
- ▶ Plunger operation with key for locking
- ▶ 100,000 mechanical operations
- ▶ 4.8 & 6.3mm tags
- ▶ Snap to panel and screw fixing
- ▶ Panel cut out: 37.0 x 13.5



C4151AA ---

**C 4151 A A - - -**

TERMINAL FUNCTION ACTUATOR BODY PRINT, COLOUR, ETC

push switches

▶ TERMINAL	▶ FUNCTION	▶ ACTUATOR	▶ BODY
<p><b>C</b></p> <p>6.3 x 0.8</p>	<p><b>Single 4101</b></p>		<p><b>A</b></p>
<p><b>H</b></p> <p>4.8 x 0.8</p>	<p><b>Double 4151</b></p> <p>OFF - ON (momentary)</p>		<p><b>B</b></p>
			<p><b>C</b></p>
			<p><b>D</b></p>

**Accessories**  
 Locking key: M1395  
 Connector: M1396

**Dimensions (mm)**  
**C4151HAA**

