

7000 Push Button Switches 16A 250Vac



- ▶ Round and rectangular push button switches
- ▶ Ratings up to 16A, 250V ac
- ▶ Latching and momentary
- ▶ Illuminated & non-illuminated
- ▶ Matching indicators
- ▶ Low profile version
- ▶ Panel cut outs:
25.0 dia
27.2 x 22.3



16(4)A 250Vac T125
8(8)A 250Vac T85




UL CSA 16A Non Ind, 250Vac 1hp, 125Vac 1/2hp
UL 65°C, file no. E45221, CSA file no. LR10990



RoHS compliant

3mm contact gap.
Technical data on pages 4 & 5 (switches), 6 (indicators).

push switches



TERMINAL	FUNCTION			ACTUATOR	
C 6.3 x 0.8 9.1	7000		Single pole ON - OFF 	A Round actuator shown in F body 	
	7001		Single pole ON - OFF (momentary ON) 		
	7003		Single pole ON - OFF with light 	B Round actuator - medium shown in F body 	
	7004		Single pole ON - OFF (momentary ON) with light 		
	H 4.8 x 0.8 9.1	7050		Double pole ON - OFF 	C Round actuator - long shown in F body
		7051		Double pole ON - OFF (momentary ON) 	
		7053		Double pole ON - OFF with light 	D Round actuator - sub panel mount
7054			Double pole ON - OFF (momentary ON) with light 		
7030			Indicator 	S Rectangular actuator Shown in "A" body N/A for 7030 	



C7000AF ---




C7003AF ---



C7053CF ---



C7053BF ---



C7050SA ---



C7053AG ---






C7053DF ---



C7030AH ---

push switches

BODY	OPTIONS
Panel cut-outs	
<p>F H G Body types fit either cut-out</p>  	<p>Finish Matt finish is standard on bodies. Gloss finish is standard on actuators.</p> <p>Colour Call sales for custom colours. A full range is available for large orders.</p> <p>Legend printing A wide range is available or call sales for custom legends.</p> <p>Lamp voltage Call sales for details of available voltages.</p> <p>Protective housing (E) (designed to IP65) Covers are available for round body styles, call sales for details.</p>
<p>A</p>  <p>Cut-outs must be punched in the direction of insertion</p>	

DIMENSIONS (mm)

Panel thickness:
A 0.8 - 2.5mm
F, G, H 0.8 - 5.0mm

