

# 0055 Door Switches



C0055RB ---

C0056RB ---



C0055RB ---

C0056RB ---

- ▶ Ratings up to 2A, 250V ac
- ▶ High temperature rating up to 125°C
- ▶ Long overtravel
- ▶ Choice of terminal orientation




**0055 & 0056**  
**0.2(0.2)A 250Vac 25T125 5E4**  
**(50,000 operations)**

**RoHS**

RoHS compliant


μ contact gap

Technical data on pages 4 & 5



▶ TERMINAL	▶ FUNCTION	▶ ACTUATOR	▶ BODY	▶ OPTIONS				
<p><b>C</b></p> <p>6.3 x 0.8</p> <p>9.1</p>	<p><b>0055</b></p> <p>ON - OFF (momentary OFF) 90° terminals</p>	<p><b>R</b></p>	<p><b>B</b></p> <p>Panel cut-out</p> <p>Panel thickness</p> <table border="1"> <tr> <td>0055</td> <td>1.0 - 1.6</td> </tr> <tr> <td>0056</td> <td>1.0 - 2.6</td> </tr> </table> <p>Flange</p>	0055	1.0 - 1.6	0056	1.0 - 2.6	<p><b>Finish</b></p> <p>Gloss finish only</p> <p><b>Colour</b></p> <p>White or black</p> <p>Call sales for custom colours.</p>
0055	1.0 - 1.6							
0056	1.0 - 2.6							
<p><b>H (0056 only)</b></p> <p>4.8 x 0.8</p> <p>9.1</p>	<p><b>0056</b></p> <p>ON - OFF (momentary OFF) Straight terminals</p>							

**Dimensions (mm)**  
**C0055RB**



**C0056RB**

