

Low Voltage Lampholders - Sealed to IP67

Colour and voltage:

These lampholders are suitable for up to 50V max.
Bulbs will be supplied (dependent on order quantity)
if a voltage is specified.

Colours - Red, Amber, Green, (Clear & Blue, check availability).


To create a catalogue number:

Refer to the 2 columns below (terminal and type), then state: Lens colour
and voltage.


- ▶ IP67 Panel seal
- ▶ Supplied complete with gaskets/'O' rings
- ▶ Up to 50V
- ▶ Red, Amber, Green, Blue and Clear
- ▶ LES, Midget Flange, MES & MBC bulb

TERM	TYPE	PANEL	ILLUM'N OPTIONS	APPROVAL
C 6.3	C1090 FPS (MES) 	19.0 4.0 max T85		
C 6.3	C1091 FQS (MBC) 	19.0 4.0 max T85		
T	T0062 AOS (Midget flange) Chrome bezel T0063 AOS (LES) Chrome bezel 	12.7 8.5 max T85		
T	T0062 MOS (LES & Midget flange) T0063 MOS (LES) 	12.7 8.5 max T85		





DIMENSIONS (mm)



Front of panel bulb replacement



Front of panel bulb replacement



F0445 MO

P.V.C. Insulating terminal cover.
For use with C1090 & C1091

