3900 Metal Lever Switches *16A 250Vac*

- Metal lever switches
- Ratings up to 20A, 277V ac
- Single and double pole
- Choice of circuits including 3 position and momentary
- 6.3mm and solder terminals
- Guard option

16(4)A 250Vac T85 (3900 & 3950)
10(4)A 250Vac T85 (All other circuits)

UL CSA 20A 125/277Vac (ON-OFF Circuits)
UL CSA 16A 125/277Vac (Other Circuits)
UL CSA 7A 72Vdc, 14A 36Vdc
UL 250Vac 1hp, 125Vac 1/2hp
UL 85˚C, file E45221, CSA file LR10990

Inrush rating - Contact factory for details

RoHS compliant

Approvals and ratings vary with function.
3mm contact gap except where marked µ.
Technical data on pages 4 & 5.

C 3900 B A - - -

TERMINAL FUNCTION ACTUATOR BODY OPTIONS

TERMINAL

C



6.3 x 0.8

T



Solder

FUNCTION

Single pole		Double pole
3900	ON - OFF	**3950**
3901	ON - OFF (momentary ON)	**3951**
3902	ON - OFF (momentary OFF)	**3952**
3910	ON - ON	**3960**
3911	ON - ON (momentary 1 side)	**3961**
3920	ON - OFF - ON µ	**3970**
3921	ON - OFF - ON µ (momentary 1 side)	**3971**
3922	ON - OFF - ON µ (momentary 2 sides)	**3972**

ACTUATOR

B



Finish is nickel plate.

C3900BA ---

C3920BA ---

Guard R17-10
Anti-rotation tab can be specified
for guard fitted in On or Off position

C3950BB ---

C3972BB ---

BODY

A
Without terminal barrier
Single pole



B
With terminal barrier
Double pole only





Panel hole (all types)

OPTIONS

Neck Seal M539
Actuator is visible

Cover M1080

Covers have internal nylon nuts

Fixing nuts

Nickel plated brass are supplied



Hex Back nut



Knurled Front nut
Panel thickness 4.0 with backnut

DIMENSIONS (mm)

* Indicates ON position (for ON - OFF switches)

Single Pole
(C terminals shown)







Optional
P232 plate
SP or DP

Double Pole
(C terminals shown)